



Product description

- OneSystem sash lock N1500 according to EN 12209 for single-leaf doors, product- specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 1,000,000 cycles and 300 kg door weight

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of escutcheons
- Suitable espagnolette integrated in the strike plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Note

- For U-shaped versions, the end caps are included in the scope of supply. Please note:, for U-shaped versions, the backset is shortened by 1 mm.

Technical data

Backset	25, 30, 35, 40, 45 mm
Distance	92 mm (prepared for Euro profile cylinders)
Face plate shape	U-shaped face plate: U6 x 24 mm Flat face plate: F3 x 20 mm, F3 x 24 mm, R3 x 20 mm, R3 x 24 mm
Material face plate	Stainless steel
DIN direction	DIN L/R (symmetrical face plate)
Bolt throw	20 mm
Standards	EN 12209
Face plate length	185, 270, 320 mm (depending on version)
Leaf type	Active door leaf
Door type	Aluminium/steel profile
Functions	mechanical
Screw type	Mortise lock
Panic function	Nein
Monitoring	No
Top locking	No
door system	Single-leaf door
Fire protection	No

